

Series 25 Audio Speaker Line

Speco Technologies' has leveraged over 45 years of residential sound expertise in developing our core in-ceiling and in-wall audio line, the Series 25. Manufactured from durable and quality components, Speco Technologies' Serial 25 Audio Speaker Line provides exceptional value. Enjoy the premium performance of full-range sound in your listening environment for countless years to come.

5.25" IN-CEILING SPEAKER

- 5.25" Polypropylene Woofer with Rubber Surround
- 3.4" Pivoting Silk Dome Tweeter
- 30 Watts RMS
- 60 Watts Max
- Frequency: 70Hz-20kHz
- Sensitivity: 87dB 1w/1m
- Impedance: 8 Ohms
- Dimensions: 8" Dia x 4" Dep
- Mounting Dimension: 65/8" Dia
- 2.4 Lbs Ea
- Sold in Pairs SP-525C
- mounting brackets BRC-5



6.5" IN-CEILING SPEAKER

- 6.5" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- 40 Watts RMS
- 80 Watts Max
- Frequency: 50Hz-20kHz
- Sensitivity: 89dB 1w/1m
- Impedance: 8 Ohms
- Dimensions: 9 1/4" Dia x 4 1/4" Dep
- Mounting Dimension: 73/4" Dia
- 3 Lbs Ea
- Sold in Pairs SP-625C
- mounting brackets BRC-6



8" IN-CEILING SPEAKER

- 8" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- 50 Watts RMS
- 100 Watts Max
- Frequency: 49Hz-20kHz
- Sensitivity: 89dB 1w/1m
- Impedance: 8 Ohms
- Dimensions: 11" Dia x 5" Dep
- Mounting Dimension: 91/2" Dia
- 4 Lbs Ea
- Sold in Pairs SP-825C
- mounting brackets BRC-8



5.25" IN-WALL SPEAKER

- 5.25" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- +/- 3Db Treble Switch
- 30 Watts RMS
- 60 Watts Max
- Frequency: 70Hz-20kHz
- Sensitivity: 87dB 1w/1m
- Impedance: 8 Ohms
- Dimensions: 75/8" W x 11" H x 3" D
- Mounting Dimension: 61/2" W x 93/8" H
- 2.7 Lbs Ea
- Sold in Pairs SP-525W
- mounting brackets BRW-5



6.5" IN-WALL SPEAKER

- 6.5" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- +/- 3Db Treble Switch
- 40 Watts RMS
- 80 Watts Max
- Frequency: 58Hz-20kHz
- Sensitivity: 88dB 1w/1m
- Impedance: 8 Ohms
- Dimensions: 83/4" W x 12 1/4" H x 3 1/2" D
- Mounting Dimension: 71/2" W x 11" H
- 3.4 Lbs Ea
- Sold in Pairs SP-625W
- mounting brackets BRW-6



8" IN-WALL SPEAKER

- 8" Polypropylene Woofer with Rubber Surround
- 1" Pivoting Silk Dome Tweeter
- +/- 3Db Treble Switch
- 50 Watts RMS
- 100 Watts Max
- Frequency: 51Hz-20kHz
- Sensitivity: 88dB 1w/1m
- Impedance: 8 Ohms
- Dimensions: 103/4" W x 14 1/2" H x 35/8" D
- Mounting Dimension: 83/4" W x 123/4" H
- 3.7 Lbs Ea
- Sold in Pairs SP-825W
- mounting brackets BRW-8



5.25" IN-WALL ENCLOSED SPEAKER SYSTEM

- 5.25" Fibreglass Woofer
- Titanium Swivel Dome Tweeter
- 55-20kHz. Frequency Response
- 40W RMS/80W Max
- 8 Ohms
- 88dB Sensitivity
- 3.6"L x 8.3"W x 11.75"H
- Cut Out Dimensions: 105/8" x 7" x 31/2"
- EZ mount tabs for easy installation
- Sold in Pairs SP-525BB



6.5" IN-WALL ENCLOSED SPEAKER SYSTEM

- 6.5" Fibreglass Woofer
- Titanium Swivel Dome Tweeter
- 50-20kHz. Frequency Response
- 60W RMS/80W Max
- 8 Ohms
- 88dB Sensitivity
- 4.25"L x 8.6"W x 12"H
- Cut Out Dimensions: 106/8" x 75/8" x 4"
- EZ mount tabs for easy installation
- Sold in Pairs SP-625BB



8" IN-WALL ENCLOSED SPEAKER SYSTEM

- 8" Fibreglass Woofer
- Titanium Swivel Dome Tweeter
- 50-20kHz. Frequency Response
- 80W RMS/80W Max
- 8 Ohms
- 88dB Sensitivity
- 4.1"L x 10"W x 14"H
- Cut Out Dimensions: 126/8" x 85/8" x 37/8"
- EZ mount tabs for easy installation
- Sold in Pairs SP-825BB



In-Wall Back Box Items (SP-525BB, SP-625BB, SP-825BB not designed to be used with support brackets)